

## Chapter 4:

# A Review and Comparative Analysis on Image Mining Techniques<sup>†</sup>

Roshani S. Nage, Vikramsingh R. Parihar\*, and Atul S. Dahane

Assistant Professor, Electrical Engineering, Prof Ram Meghe College of Engineering and Management, Amravati, India

Submitted: Oct. 10, 2018 — Accepted: Dec. 13, 2018 — Published: Dec. 30, 2018

**Abstract**—This paper presents the analysis and comparison of existing literature relevant to various image mining process and the mechanisms associated with it. Though, the literature consists of a lot many research contributions, but, here, we have critically and exhaustively analyzed forty research and review papers. Based on the basic concepts used in their mechanisms, the existing approaches are categorized into three types, image analysis and pattern recognition related work, image mining through various approaches, and graph theory based related work in image mining. The emphasis is on the concept used by the concerned authors, the database used for experimentations and the performance evaluation parameters. The claims of the researchers are also highlighted. Our findings from the exhaustive literature review are mentioned along with the identified problems. This paper is very important for the comparative study of various image mining approaches which is prerequisite for solving image mining problem.

**Keywords**—Image Analysis; Image Mining; Image Processing; Image Segmentation; Weighted Substructure.

## I. INTRODUCTION

Image analysis is the process of retrieving data or useful information from digital images by using digital image processing techniques. Image analysis can include such tasks as finding shapes, detecting edges, counting objects, or measuring properties of an object. Image mining normally deals with the study and developments of new technologies that allows image analysis. Image mining is, thus, an extended branch of data mining that is concerned with the process of knowledge discovery concerning digital images. It is concerned with the extraction of implied knowledge and image with data relationship or other patterns which are not overtly stored in the images.

Fig. 1 shows the general image mining process. The quality of database images is first improved by suitable preprocessing. The important features of the images are generated by various transformations and feature extraction processes. Using data mining techniques mining can be carried out with the aid of generated features, to discover significant patterns. The resulting patterns are interpreted to obtain the final knowledge, which can be applied to further applications.

The problem, here, is modeled in terms of creating a dataset of images and extracting the features of each image.

Then graphs are then generated for each image based on these features. The weight factor is used to measure the actual importance of each different substructure in a given graph dataset. On the basis of weighted substructure graphs the image mining process is done. For image mining, an external query image is to be provided by user. Its features are extracted and graph is generated. Later the substructure of query image is matched with the substructure of the dataset. The most closely matched substructures of images from the dataset are identified and it can be concluded that the identified images are close to the query image.

## II. LITERATURE REVIEW

This section presents the critical analysis of existing literature which is relevant to image mining and the mechanisms associated with it. Though, the literature consists of a lot many research contributions, but, here, we have analyzed forty research and review papers. The existing approaches are categorized based on the basic concepts involved in the mechanisms. The emphasis is on the concepts used by the concerned authors, the data-base used for experimentations and the performance evaluation parameters (PEP). Their claims are also highlight-ed. Finally, the findings are summarized related to the studied and analyzed research papers.

\* Corresponding Author: Vikramsingh R. Parihar, *PhD*

E-mail: [vikramsingh.parihar@prnceam.ac.in](mailto:vikramsingh.parihar@prnceam.ac.in)

<sup>†</sup> Book Chapter (ImgSeq 2018: Image Segmentation: A Guide to Image Mining)

© 2018 International Computer Science and Engineering Society (ICSES)




Figure 1. The general process of image mining

#### A. Image Analysis and Pattern Recognition Related Work

In the year 2007, researchers [1] introduced a feature selection algorithm i.e. Maximal Marginal Relevance Feature Selection (MMRFS) algorithm to select discriminative frequent patterns. The method is able to overcome two kinds of overfitting problems and is shown to be scalable. They claim that the frequent patterns are high quality features and have good model generalization ability. The framework is also applicable to more complex patterns, including sequences and graphs. They used performance evaluation parameters like accuracy and time and carried out experimentations on Standard database. It is identified that feature selection algorithm takes more time to execute.

Researchers develop an algorithm using multiple segmentations to discover objects and their extent in image collections [2]. They used the performance evaluation parameters of average precisions. They carried out experimentations on Cal tech, MSRC and LabelMe database. It is identified that the visual quality of images is not good due to overlapping of segment.

In year 2003, researchers [3] introduced a approach which applies the EMD to texture extraction and image filtering. They developed an algorithm based on bidimensional empirical mode decomposition (BEMD) to extract features at multiple scales or spatial frequencies. They carry out the experimentation on synthetic and natural images and used the performance evaluation parameter of frequency components. They claim that results are good for both synthetic and natural images. EMD gives a new and promising way to decompose and extract texture features without parameter. However, their work does not concentrate on entire images at a time.

In year 2010, researchers worked on image analysis algorithms and visualization [4]. He used the performance evaluation parameters of true positive fraction (TPF), false positive fraction (FPF) and showed that all mentioned applications<sup>0</sup> which are useful for image analysis.

In the year 2003, researchers [5] proved that the Krawtchouk moments can be employed to extract local features of an images. Krawtchouk moments are a set of moments which formed by using Krawtchouk polynomials called as the basis function set. They carried out the experimentation on Uppercase letters and Lowercase letters. They used noise, density, Hu, Krawtchouk as the performance evaluation parameters for their approach. They claim that in object recognition experiment, the results show Krawtchouk moment invariants perform significantly better than Hu's moment invariant. And also perform better in terms of reconstruction error. However, computational time evaluation is not presented.

Researchers [6] introduced the model-based approaches including elastic bunch graph matching, active appearance model and 3D morphable model methods. He also provided appearance-based method and model-based face recognition method. Appearance-based face recognition method is applicable to only low resolution or poor quality images. The model-based method has intrinsic physical relationship with real faces. An explicit modeling of face variations, such as pose, illumination and expression, gives the possibility to handle these variabilities in practice. He used performance evaluation parameter like error rate, recognition accuracy, Computation (floating-point operations).

The systematic representation of above image analysis related work is given in Table I.

**TABLE I**  
SUMMARY OF PATTERN RECOGNITION AND IMAGE ANALYSIS RELATED WORK

Sr. No	Ref. no. Author(s) & year	Concept used	Performance Evaluation Parameter	Database used	Claims by Concerned Author(s)	Our findings
01	[1] Hong Cheng, Xifeng Yan et al. 2007	A feature selection algorithm is introduced to select discriminative frequent patterns.	Accuracy, Time.	Standard	Frequent patterns are high quality features and have good model generalization ability. The framework is also applicable to more complex patterns, including sequences and graphs.	Feature selection algorithm takes more time to execute.
02	[2] Bryan Russell Alexei Efros et al. 2006.	Developed an algorithm using multiple segmentations to discover objects and their extent in image collections	Average precisions.	Cal tech, MSRC and LabelMe	Their results are computed from a small set of single object category images.	Visual quality of images is not good due to overlapping of segment.
03	[3] J.C. Nunes, Y. Bouaoune, E. Delechelle, O. Niang. 2003	The EMD is applied to texture extraction and image filtering, then an algorithm is developed based on bidimensional empirical mode decomposition to extract features at spatial frequencies	Frequency components.	Synthetic and natural images	Result are good for both synthetic and natural images. EMD gives a new and promising way to decompose and extract texture features without parameter.	The mentioned method does not concentrate on entire images at a time.
04	[4] Dougherty G. 2010	Image analysis algorithms and visualization.	True positive fraction, False positive fraction.	Not mentioned	All application which are mentioned in paper are useful for image analysis.	Requires more user interaction

### B. Image mining through various approaches

In the year 2013, researchers [7] carried out a survey in need of image mining and techniques. They provide various techniques used for image mining applications like image retrieval, matching, pattern recognition etc. However, they fail to mention the details regarding each technique separately and addressed the existing methods in a general manner.

Researchers introduced the concept of extract patterns and derive knowledge from large collections of images, and also extract unique features for the images [8]. They used the parameters of recall and precision for comparison with other approaches. They claim that the features used are sufficient to identify the patterns from the images and tested images required less human interaction for resolving the uncertain regions. However, the detection process is carried out manually, which is laborious and time consuming.

Researchers [9] used feature mining paradigm for image classification and examine several feature mining strategies. They used the performance evaluation parameters like True positive (TP), False positive (FP), computation time. They carried out experimentations on MIT CBCL face data-set. They claim that the proposed approach provides effective result for feature mining. However, computational complexity of the algorithm seems to be more as time estimation is not presented.

Researchers [10] presented a method for frequently occurring mining objects and scenes from videos. Video data mining is based on the detection of recurring spatial arrangements of local features; these features are represented in quantized codebooks. They claim that their approach is suitable and efficient tool for video mining. However, the mentioned approach fails in high resolution video mining technique and performance evaluation parameter is not given.

Researchers worked on video data mining using configurations of viewpoint invariant regions [11] and also work on extract significant objects, characters and scenes in a video by determining the frequency of occurrence of spatial configurations. They used the parameters of precision and recall for comparison with other approaches. They claimed that textured region provides good results for video mining. However, they discussed only about textured regions and other regions are missed.

In the year 2010, researchers [12] worked on image retrieval technique based on optimum clusters for improving user interaction with image retrieval systems by fully exploiting the similarity information. In content based image retrieval (CBIR) image mining process can be done in following steps: The images from an image database are first preprocessed to improve their quality. These images then go through various transformations and feature extraction to generate the important features from the images. With the generated features, mining can be carried out using data mining techniques to discover significant patterns. The resulting patterns are evaluated and interpreted to obtain the final knowledge, which can be applied to applications. They used performance evaluation parameter as precision and recall. They claim that the the proposed method is very useful for image mining. By using this method one can easily find out the similar images related to query image and cbir provides good result. However, in CBIR the features of the query image alone are considered; database is also not given.

Researchers [13] carried out a survey of image mining which provides the research issues in image mining, current developments in image mining, image mining frameworks, state of the art techniques and systems. However, they fail to mention the details regarding each approach separately and addressed the existing methods in a general manner.

In the year 2013, researchers [14] show that mining of strongly correlated subgraph patterns is done by considering weight and support constraints. Weighted frequent graph mining is an approach for applying importance of objects in the real world to the graph mining. They used runtime, minimum threshold as performance evaluation parameter and carry out experimentations on PTE dataset and DTP dataset. They claim that MSCG algorithm not only mined meaningful patterns with strong correlation among the elements in sub-graphs efficiently but also have advanced performance as reducing search space by the mentioned measure. However, complexity is more and time required for the algorithm to execute seems to be more.

In [15], researchers in the year 2005, proposed a general hierarchical image classifier approach, and illustrates the ease with which it can be trained to find objects in a scene. This application area required a method which allowed the detection of objects trained from image patches, and also enabled arrangements of component detectors for image mining. The performance evaluation parameter used are Positive count, Negative count, False positive count (FPC), False negative count (FNC). They carried out their experimentations on Biology and Vietnamese art images. However, features of images are not mentioned.

In the year 2003, researchers [16] introduced a concept of a prototype of a knowledge driven content-based information mining system produced to manage and explore large volumes of remote sensing image data. They used performance evaluation parameter as size, resolution and signal models and carry out their experimentations on EU SC, NERSC database. They claimed that the presented approach is KIM, which is a prototype of a next-generation knowledge-driven image information mining system developed for the exploration of large image archives. However, computational complexity of the algorithm seems to be more as time estimation is not presented.

In the year 2011, researchers worked on new method for detecting images [17], and used the method Lorenz Information Measure (LIM) for representing features extracting from the images for retrieval. Their mentioned approach attempts to make the process mostly independent of any parameter setting to generate a robust solution. They used sample test, image database used, time as performance evaluation parameter. They claimed that the image mining system derived from the LIM based image matching technique provided promising results, which are comparable and significant. However, time required for the algorithm to execute seems to be more.

Researchers [18], introduced an effective method for image classification using itemset mining to discover a new set of mid-level features called Frequent Local Histograms (FLH). They used the parameters like Classification accuracy, equal error rate, mean average precision for performance evaluation. And carry out their experimentation on GRAZ-01, Oxford-Flowers, 15-Scenes and the PASCAL-VOC2007 dataset.

However, the differences between the results of mentioned approach and other methods are not very obvious in case of the images which contain a large amount of edge details.

Researchers [19], proposed a novel array based technique that greatly reduces the need to traverse FP-trees and also present new algorithms for a number of common data mining problems. Also present an algorithm, FPclose, for mining closed frequent item sets. FPclose uses yet another variation of the FP-tree structure for checking the closeness of frequent item sets. They carry out the experimentation on sparse, synthetic and real datasets and used the performance evaluation parameter CPU Time(s), Minimum Support (%), Main Memory (M). They claim that all algorithms i.e. FPgrowth, FPmax, FPclose need less main memory because of the compact FP-trees, MFI-trees, and CFI-trees.

In the year 2008, researchers introduced an efficient method for frequent pattern mining [20] and showed how the different approaches achieve the objective of frequent mining. The process of data mining is helpful in generation of support systems that can help in various fields. They used Time, Space as performance evaluation parameter and carried out the experimentation on Sparse and dense databases. They claimed that Apriori is the simplest and best algorithm for mining of frequent patterns from the transaction database. However, Prefix tree approach is better in performance as compared to Apriori.

Researchers [21], proposed work in the following steps; A large size (~391k) human aging image database was crawled via a set of popular age related queries in first step. Then, after parallel detection and noise removal, a clean database with about 220k face instances is obtained. Finally, a robust multiple instance regressor learning method was developed for handling both noisy images and label. They used performance evaluation parameters like Mean absolute errors (MAEs), Age distribution statistics and carried out experimentations on Benchmark datasets, FG-NET UIUC etc. They claimed that automatic web image mining system towards building a universal human age estimator based on facial information, which is applicable to all ethnic groups and various image qualities, providing best result. However, before automatically obtained age information, a training set is required to be created which requires much amount of efforts and time.

In the year 2013, researchers [22], worked for to find the feature extraction then finding the clusters of image with K-mean and after that finding the sequence of the image. Their approach is based on two categories i.e. abrupt change in intensity and portioning. They used time as performance evaluation parameter. They claimed that the mentioned approach gives better results in sequencing of images by using Spade Algorithm. However, the approach requires more user interaction.

The systematic representation of above mining fundamental related work is given in Table II.

**TABLE II**  
SUMMARY OF MINING THROUGH VARIOUS APPROACHES

Sr. No	Ref. no. Author(s) & year	Concept used	Performance Evaluation Parameter	Database used	Claims by Concerned Author(s)	Our findings
01	[8] Patricia G. Foschi, Deepak Kolippakkam, et al. 2002.	Extract patterns and derive knowledge from large collections of images, and also extract unique features for the images.	Precision, Recall	Not mentioned	The features used are sufficient to identify the patterns from the Images. and tested images required less human interaction for resolving the uncertain regions.	The detection process has been carried out manually, which is laborious and time consuming.
02	[9] Piotr Dollar Zhuowen Tu et al. 2007	Feature mining paradigm for image classification and examine several feature mining strategies.	True positive False positive, computation time	MIT CBCL face data-set	This approach provides effective result for feature mining.	Systems use features of homogeneous type and computational complexity.
03	[10] Till Quack, Vittorio Ferrari, et al. 2006	Video Mining with Frequent Itemset Configurations.	None	Not mentioned	Mining approach based on frequent item sets is a suitable and efficient tool for video mining.	The mentioned approach fails in high resolution video mining technique.
04	[11] Josef Sivic and Andrew Zisserman. 2004.	Extract significant objects, characters and scenes in a video by determining the frequency of occurrence of spatial configurations	Precision, recall	None	Textured region provides good results for video mining.	They only discussed about textured regions and other regions are missed.
05	[12] A.Kannan , Dr.V.Mohan Dr.N.Anbazhagan. 2010	Image retrieval based on optimum clusters is proposed for improving user interaction with image retrieval systems by fully exploiting the similarity information.	Precision and Recall	None	The mentioned method is very useful for image mining. By using this method we can easily find out the similar images related to query image.	In CBIR the features of the query image alone are considered .
06	[13] Ji Zhang Wynne Hsu Mong Li Lee. 2001	The research issues in image mining, current developments in image mining, image mining frameworks, state-of-the-art techniques and systems.	None	Not mentioned	Gives two frameworks for image mining: function-driven and information-driven image mining frameworks. Both are useful for image mining technique.	Visual quality is not so good. So use of new visualization techniques for the visualization of image patterns is needed.
07	[14] Gangin Lee and Unil Yun 2013.	Mining strongly correlated sub-graph patterns by considering weight and support constraints	Runtime, Minimum threshold.	PTE dataset, DTP dataset.	MSCG algorithm not only mined meaningful patterns with strong correlation among the elements in sub-graphs efficiently but also advanced performance as reducing search space by the proposed measure.	Complexity is more and time required for the algorithm to execute seems to be more.
08	[15] R. Brown, B. Pham. 2005	Used a general hierarchical image classifier approach, and illustrates the ease with which it can be trained to find objects in a scene.	Positive count, Negative count, False positive count, False negative count.	Biology and Vietnamese art images.	Capabilities of this approach is more as compare to other classifier.	Features of images are not mentioned.
09	[16] Mihai Datcu, Herbert Daschiel, et al. 2003.	A concept of a prototype of a knowledge driven content-based information mining system produced to manage and explore large volumes of remote sensing image data.	Size, resolution, signal models.	EU SC, NERSC	The mentioned approach is KIM, which is a prototype of a next-generation knowledge-driven image information mining system developed for the exploration of large image archives.	computational complexity of the algorithm seems to be more as time estimation is not presented.
10	[17] C. Lakshmi Devasena, M. Hemalatha. 2011.	A hybrid image mining technique using LIM-based data mining algorithm.	Sample test, Image database used, Time.	Not mentioned	They claimed that the image mining system derived from the LIM based image matching technique provided promising results, which are comparable and significant.	Time required for the algorithm to execute seems to be more.
11	[18] Basura Fernando, Elisa Fromont and Tinne Tuytelaars. 2012.	An effective method for image classification using itemset mining is introduced to discover a new set of mid-level features called Frequent Local Histograms (FLH).	Classification accuracy, Equal error rate, Mean average precision.	GRAZ-01, Oxford-Flowers, 15-Scenes and the PASCAL-VOC2007 dataset.	They claim that their relevant pattern mining method and the chosen kernel all improve the classification results on various datasets.	The differences between the results of mentioned approach and other methods are not very obvious in case of the images which contain a large amount of edge details.

12	[19] Gosta Grahne and Jianfei Zhu, 2003.	A novel array based technique that greatly reduces the need to traverse FP-trees and also present new algorithms for a number of common data mining problems.	CPU Time(s), Minimum Support (%), Main Memory (M).	Sparse , Synthetic and real datasets.	They claim that all algorithms i.e. FPgrowth, FPmax FPclose need less main memory because of the compact FP-trees, MFI-trees, and CFI-trees.	FPclose algorithm is good in to generates more non-closed frequent itemsets than the other algorithms.
13	[20] Vaibhav Kant Singh, Vijay Shah, et al. 2008.	An efficient method for frequent pattern mining is introduced.	Time, Space.	Sparse and dense.	Apriori is the simplest and best algorithm for mining of frequent patterns from the transaction database.	Prefix tree approach is better in performance as compared to Apriori.
14	[21] Bingbing Ni, Zheng Song, Shuicheng yan. 2009	They carried out their work in the following steps. A large size (~391k) human aging image database was crawled via a set of popular age related queries in first step. Then, after parallel detection and noise removal, a clean database with about 220k face instances is obtained. Finally, a robust multiple instance regressor learning method was developed for handling both noisy images and label.	Mean absolute errors (MAEs), Age distribution statistics.	Benchmark datasets, (FG-NET UIUC etc)	An automatic web image mining system towards building a universal human age estimator based on facial information, which is applicable to all ethnic groups and various image qualities. And providing best result.	Before automatically obtained age information , a training set is required to be created which requires much amount of efforts and time
15	[22] Harsh mathur 2013.	Basic concept is to find the feature extraction then finding the clusters of image with K-mean and after that finding the sequence of the image.	Time	Not mentioned	Gives better results in sequencing of image by using Spade Algorithm.	Requires more user interaction.

### C. Graph Theory Related Work in Image Mining

In the year 2006, researchers [23], worked on clustering graphs. This work presented an approach to combine probabilistic inference and graph mining using simple mixture model. For general applications with insufficient domain knowledge, it is difficult to select the patterns manually in advance. They used frequent substructure mining methods to find the set of patterns that appear frequently in the database. They used computational time as a performance evaluation parameter. However, time required for the algorithm to execute seems to be more.

Researchers in year 2004, proposed an application of Boosting for classifying labeled graphs, general structures for modeling a number of real world data [24] and also discussed the relation between mentioned algorithm and SVMs with convolution kernels. The performance evaluation parameter used by them is REV, PTC and BOL (bag-of-label). They claimed that the boosting algorithm is accurate and efficient for classification tasks involving discrete structural features. However, though the speed of boosting algorithm is fast but it seems that it is computationally complex.

In the year 2002, researchers introduce an algorithm called gSpan (graph-based Substructure pattern mining), which gives frequent substructures without candidate generation. gSpan builds a new lexicographic order among graphs, and maps each graph to a unique minimum DFS code as its canonical label [25]. Frequent substructure pattern mining has been a rising data mining problem with many scientific and commercial applications. They used Depth-First Search Tree as performance evaluation parameters and carried out their experimentations on Synthetic Datasets, Chemical Compound

Dataset. However, computational complexity of the algorithm seems to be more as time estimation is not presented.

In the year 2012, researchers [26] used the path following algorithm to matching problems on directed graph models. Based on the concave and convex relaxations, they used PATH following algorithm to cover graphs. The performance evaluation parameter used by them are Mean, standard deviation, optimal matching. They carried out their experimentations on benchmark data set. They claimed that some experimental comparisons show the mentioned method is valid and good. However, Concave relaxation is better to solve matching problem than path following algorithm.

Researchers, in year 2000, presented a Graph-based representations and approaches for image processing and image analysis [27] and carried out their work in the following steps. In first step present a generalization of a graph partitioning greedy algorithm for colour image segmentation. Next describe a novel fusion of colour based segmentation and depth from stereo that yields a graph representing every object in the scene. Finally describe a new representation of a set of attributed graphs (AGs), denominated function described graphs (FDGs), a distance measure for matching AGs with FDGs and some applications for robot vision. They used Recognition ratio as a performance evaluation parameter and carried out their experimentations on Libor Spacek's database. However, computational time is not evaluated.

In the year 2005, researchers [28], worked on a spectral method which used to partition graphs into non- overlapping subgraphs both for matching and clustering. They carried out their experimentations on Real word data. And used the performance evaluation parameters like House index, corners, correct, false, missed. They claim that the problem of matching

the graphs into that of matching structural subunits can solve by using Fiedler vector of the Laplacian matrix.

Researchers, in year 2013, worked on the weighted graph matching problem with partially disclosed correspondences between a number of anchor nodes solve by using integer quadratic program (IQP) [29]. Their work provides max-margin formulation makes an effective use of the scarce training data even a small number of known correspondences leads to a large number of constraints on the proximity matrix. They used average, accuracy as the performance evaluation parameters. They claimed that they obtained superior performance as compared to the state of the art techniques based on adjacency matrices. However, they have not mentioned computational time for performance evaluation.

In the year 2012, researchers [30] present PdEs-based morphology on graphs for cytological slides segmentation and clustering. They gave three methods for applications to cytology as first method - Papanicolaou coloration, Second method -Feulgen coloration and third method - Data Clustering. They claim that the approach is very general and has been illustrated through two methodologies, using different graph-based image representations.

In the year 2011, researchers [31] introduce an adaptation of PDEs level sets over weighted graphs of arbitrary structure, based on PdEs and using a frame- work of discrete operators. They claim experimental results have shown the potentiality of the proposed formulation of PDEs level sets and its adaptivity to graphs of arbitrary topology.

In 2006, researchers [32] provides minimal invariant sets in a vertex weighted graph. An invariant set is an edge set such that the sum of the weights of its edges is the same for every edge weighting. A complete axiomatisation of invariant sets is stated and give a polynomial algorithm to find a set of minimal invariant sets that completely characterize the set of all invariant sets. They carry out their experimentation on Statistical database. They claim that a graphical characterization of minimal invariant sets and a complete axiomatization of invariant sets both provides good result. However, Performance evaluation parameters are not given.

Researchers [33], proposed a general formulation of discrete functional regularization on weighted graphs. For providing fast image segmentation, they had also proposed a graph based image simplification. Variational methods, based on regularization, provide a framework to handle image processing problems by designing and solving Partial Differential Equations (PDEs) in continuous domain. Then, PDEs are discretized in order to fit with the image domain. They claim that they provide two classification approaches. Both approaches can be applied in a wide range of applications in various domains, for instance data sets analysis or clustering. However, performance evaluation parameter and database are not mentioned.

The systematic representation of above graph related work is given in Table III.

**TABLE III**  
SUMMARY OF GRAPH THEORY BASED RELATED WORKS IN IMAGE MINING

Sr. No	Ref. no. Author(s) & year	Concept used	Performance Evaluation Parameter	Database used	Claims by Concerned Author(s)	Our findings
1	[23] Koji Tsuda and Taku Kudo, 2006.	The work present an approach to combine probabilistic inference and graph mining using simple mixture model.	Computation time	Not mentioned	It is possible to extend the learning method for more advance probabilistic model. And if tree mining is used instead of graph mining, the time will be much shorter.	Time required for the algorithm to execute seems to be more.
2	[24] Taku Kudo, Eisaku Maeda, Yuji Matsumoto, 2004	Decision stumps that use sub-graph as features, and a Boosting algorithm in which sub-graph-based decision stumps are used as weak learners.	REV , PTC and BOL	None	Boosting algorithm is accurate and efficient for classification tasks involving discrete structural features.	Though the speed of boosting algorithm is fast but it seems that it is complicated to understand.
3	[25] Xifeng Yan Jiawei Han, 2002	Propose a novel algo- rithm called gSpan(graph-based Substructure pattern min- ing), which gives frequent substructures without candidate generation. gSpan builds a new lexicographic order among graphs, and maps each graph to a unique mini- mum DFS code as its canonical label.	Depth-First Search Tree	Synthetic Datasets, Chemical Compound Dataset.	gSpan outperforms FSG by an order of magnitude and is capable to mine large frequent subgraphs in a bigger graph set with lower minimum supports	Requires a lot of user interaction, computational complexity of the algorithm seems to be more as time estimation is not presented.

4	[26] Zhi-Yong Liu, Hong Qiao, and Lei Xu, Fellow, 2012	Used the path following algorithm to matching problems on directed graph models. Based on the concave and convex relaxations.	Mean, standard deviation, optimal matching.	Benchmark data set	Some experimental comparisons shows the proposed method is valid and good	Concave relaxation is better to solve matching problem than path following algorithm.
5	[27] A.Sanfeliua, R. Alquezarb et al 2000	Graph-based representations and approaches for image processing and image analysis	Recognition ratio	Libor Spacek's database, University of Essex.	Graph approaches permit to represent objects in very natural way, without critical losses.	Computational time is not evaluated
6	[28] Huaijun Qiu and Edwin R. Hancock, 2005.	A spectral method which used to partition graphs into non-overlapping subgraphs both for matching and clustering.	House index, corners, correct, false, missed.	Real word data	The problem of matching the graphs into that of matching structural subunits can solve by using Fiedler vector of the Laplacian matrix.	Hierarchical matching method does not destroy cluster structure.
7	[29] Nan Hu Raif M. Rustamov Leonidas Guibas, 2013.	The weighted graph matching problem with partially disclosed correspondences between a number of anchor nodes solve by using integer quadratic program (IQP).	Average, Accuracy.	Not mentioned	Obtained superior performance as compared to the state-of-the-art techniques based on adjacency matrices.	They claimed that they obtained superior performance but they does not mentioned computational time for performance.
8	[30] Xavier Desquesnes, Abderrahim Elmoataz and Olivier Lezoray 2012.	PdEs-based morphology on graphs for cytological slides segmentation and clustering.	None	None	The mentioned approach is very general and has been illustrated through two methods, using different graph-based image representations. In both cases, the proposed methodologies has given very good and promising results.	Feulgen coloration method requires more user interaction due to more complexity.
9	[31] Xavier Desquesnes, Abderrahim Elmoataz and Olivier Lezora. 2011	A adaptation of PDEs level sets over weighted graphs of arbitrary structure, based on PdEs and using a framework of discrete operators	Not mentioned	None	Experimental results have shown the potentiality of the proposed formulation of PDEs level sets and its adaptively to graphs of arbitrary topology.	Sometime PDE based front propagation formulation enables the processing of a huge variety of discrete data.
10	[32] Francesco M. Malvestuto*, Mauro Mezzini, Marina Moscarini. 2006	Minimal invariant sets in a vertex-weighted graph. An invariant set is an edge set such that the sum of the weights of its edges is the same for every edge weighting,	Not mentioned	Statistical database	A graphical characterization of minimal invariant sets, and a complete axiomatization of invariant sets both are provides good result.	Performance evaluation parameters are not given.
11	[33] Vinh Thong Ta, Olivier Lezoray, and Abderrahim Elmoataz, 2007.	Author propose a general formulation of discrete functional regularization on weighted graphs. For providing a fast image segmentation they had also proposed a graph based image simplification.	None	Not mentioned	Provides two classification approaches. Both approach can be applied in a wide range of applications in various domains, for instance data sets analysis or clustering.	It requires more user interaction and also computational complexity seems to be more as no evaluation of time is presented.

### III. FINDINGS FROM STUDIED LITERATURE

There is a large literature on image mining, dating back over 20 years, with applications in Web Related Image Searching, Image Classification, and many areas other than computer vision as well. However, here, we have critically analyzed around forty review and research papers. The findings from this exhausting literature review are summarized below:

- Mining approach has faster execution time and more compact memory usage due to weighted substructure.
- Graph approaches permit to represent objects in very natural way, without critical losses.

- Mining approach based on frequent item sets is a suitable and efficient tool for video mining.
- MSCG algorithm not only mined meaningful patterns with strong correlation among the elements in sub-graphs efficiently but also advanced performance as reducing search space by the proposed measure.
- gSpan outperforms FSG by an order of magnitude and is capable to mine large frequent subgraphs in a bigger graph set with lower minimum supports
- Boosting algorithm is accurate and efficient for classification tasks involving discrete structural features.

#### IV. IDENTIFIED PROBLEMS

In any web search application when we try to search a particular image we get the irrelevant images compare to our search.

- It is very difficult task to sort image automatically in given database. Image can be model as the collection of parts.
- In image there is some pattern that can appear frequently. This frequent pattern is to be discriminative for telling apart samples of different classes.
- By identifying discriminative patterns in collection of image we mine the item (image).
- There is lot of working has been done for classification of images by using discriminative frequent pattern analysis.
- By using frequent pattern analysis, we can retrieve our relevant searched image from given set of images (database).
- It is possible to avoid outlier (irrelevant) images by using algorithms which can identify these images automatically.

#### V. DISCUSSION

Existing literature is summarized based on the content of the relevant research papers, Finally, the findings are identified for the same research papers. Gist of the studied research papers is presented in three categories, namely, Image analysis related work, mining fundamental related work, and graph theory based work.

#### VI. CONCLUSION

This paper provided the direction to solve the image mining problem through various approaches. Presented work is very useful to the beginners in the domain of image processing, particularly who want to work in the image mining and image analysis.

#### REFERENCES

- [1] H. Cheng, X. Yan, J. Han, and C.-W. Hsu, "Discriminative Frequent Pattern Analysis for Effective Classification," *2007 IEEE 23rd International Conference on Data Engineering*, Apr. 2007.
- [2] B. C. Russell, W. T. Freeman, A. A. Efros, J. Sivic, and A. Zisserman, "Using Multiple Segmentations to Discover Objects and their Extent in Image Collections," *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, vol. 2 (CVPR'06).
- [3] J. Nunes, Y. Bouaoune, E. Delechelle, O. Niang, and P. Bunel, "Image analysis by bidimensional empirical mode decomposition," *Image and Vision Computing*, vol. 21, no. 12, pp. 1019–1026, Nov. 2003.
- [4] G. Dougherty, "Image analysis in medical imaging: recent advances in selected examples," *Biomedical Imaging and Intervention Journal*, vol. 6, no. 3, Jul. 2010.
- [5] Pew-Thian Yap, R. Paramesran, and Seng-Huat Ong, "Image analysis by krawtchouk moments," *IEEE Transactions on Image Processing*, vol. 12, no. 11, pp. 1367–1377, Nov. 2003.
- [6] X. Lu, "Image Analysis for Face Recognition," *Personal Notes*, May 2003.
- [7] A.Hema, and E.Annasaro, "A survey in need of image mining techniques," *International Journal of Advanced Research in Computer and Communication Engineering*, vol. 2, no. 2, pp. 1238-1240, Feb. 2013.
- [8] P. G. Foschi, D. Kolippakkam, H. Liu, and A. Mandvikar, "Feature Extraction for Image Mining," *Proceedings in International workshop on Multimedia Information System*, pp. 103-109, Oct. 2002.
- [9] P. Dollar, Z. Tu, H. Tao, and S. Belongie, "Feature Mining for Image Classification," *2007 IEEE Conference on Computer Vision and Pattern Recognition*, Jun. 2007.
- [10] T. Quack, V. Ferrari, and L. Van Gool, "Video Mining with Frequent Itemset Configurations," *Image and Video Retrieval*, pp. 360–369, 2006.
- [11] J. Sivic and A. Zisserman, "Video data mining using configurations of viewpoint invariant regions," *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2004. CVPR 2004.
- [12] A. Kannan, V. Mohan, and N. Anbazhagan, "An Effective Method of Image Retrieval using Image Mining Techniques," *The International journal of Multimedia & Its Applications*, vol. 2, no. 4, pp. 17–26, Nov. 2010.
- [13] J. Zhang, W. Hsu, and M. Li Lee, "Image Mining: Issues, Frameworks and Techniques", In *Proceedings of the Second International Conference on Multimedia Data Mining*. Springer-Verlag, pp. 13-20, 2001.
- [14] G. Lee, and U. Yun, "Mining Strongly Correlated Sub-Graph Patterns by Considering Weight and Support Constraints," *International Journal of Multimedia and Ubiquitous Engineering*, vol. 8, no. 1, pp. 197-206, Jan. 2013.
- [15] R. Brown and B. Pham, "Image Mining and Retrieval Using Hierarchical Support Vector Machines," *11th International Multimedia Modelling Conference*.
- [16] M. Datcu, H. Daschiel, A. Pelizzari, M. Quartulli, A. Galoppo, A. Colapicchioni, M. Pastori, K. Seidel, P. G. Marchetti, and S. D'Elia, "Information mining in remote sensing image archives: system concepts," *IEEE Transactions on Geoscience and Remote Sensing*, vol. 41, no. 12, pp. 2923–2936, Dec. 2003.
- [17] C. Lakshmi Devasena and M. Hemalatha, "A Hybrid Image Mining Technique using LIMbased Data Mining Algorithm," *International Journal of Computer Applications*, vol. 25, no. 2, pp. 1–5, Jul. 2011.
- [18] B. Fernando, E. Fromont, and T. Tuytelaars, "Effective Use of Frequent Itemset Mining for Image Classification," *Lecture Notes in Computer Science*, pp. 214–227, 2012.
- [19] G. Grahne, and J. Zhu, "Efficiently Using Prefix-trees in Mining Frequent Itemsets", *Proceedings of FIMI'03 Workshop on Frequent Itemset Mining Implementations*, pp. 127-136, Nov. 2003.
- [20] V. K. Singh, V. Shah, Y. K. Jain, A. Shukla, A.S. Thoke, V. K. Singh, C. Dule, and Vivek Parganiha, "Proposing an Efficient Method for Frequent Pattern Mining," *International Journal of Biotechnology and Bioengineering*, vol. 2, no.12, 2008.
- [21] B. Ni, Z. Song, and S. Yan, "Web image mining towards universal age estimator," *Proceedings of the seventeen ACM international conference on Multimedia - MM '09*, 2009.

- [22] H. Mathur, "Sequential Mining of Multimedia Images by using SPADE Algorithm," *International Journal of Computer Science and Information Technologies (IJCSIT)*, vol. 4, no. 6, pp. 791-795, 2013.
- [23] K. Tsuda and T. Kudo, "Clustering graphs by weighted substructure mining," *In proceedings of the 23rd international conference on Machine learning - ICML '06*, 2006.
- [24] T. Kudo, E. Maeda, and Y. Matsumoto, "An Application of Boosting to Graph Classification," *17th Annual Conference on Neural Information Processing Systems (NIPS 2004)*, pp. 729-736, 2004.
- [25] Xifeng Yan, and Jiawei Han, "gSpan: graph-based substructure pattern mining," *2002 IEEE International Conference on Data Mining*, 2002. Proceedings.
- [26] Z.-Y. Liu, H. Qiao, and L. Xu, "An Extended Path Following Algorithm for Graph-Matching Problem," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 34, no. 7, pp. 1451-1456, Jul. 2012.
- [27] A. Sanfeliu, R. Alquézar, J. Andrade, J. Climent, F. Serratos, and J. Vergés, "Graph-based representations and techniques for image processing and image analysis," *Pattern Recognition*, vol. 35, no. 3, pp. 639-650, Mar. 2002.
- [28] H. Qiu and E. R. Hancock, "Graph matching and clustering using spectral partitions," *Pattern Recognition*, vol. 39, no. 1, pp. 22-34, Jan. 2006.
- [29] N. Hu, R. M. Rustamov, and L. Guibas, "Graph Matching with Anchor Nodes: A Learning Approach," *2013 IEEE Conference on Computer Vision and Pattern Recognition*, Jun. 2013.
- [30] X. Desquesnes, A. Elmoataz, and O. Lezoray, "PdEs-based morphology on graphs for cytological slides segmentation and clustering," *2012 9th IEEE International Symposium on Biomedical Imaging (ISBI)*, May 2012.
- [31] X. Desquesnes, A. Elmoataz, and O. Lezoray, "PDEs level sets on weighted graphs," *2011 18th IEEE International Conference on Image Processing*, Sep. 2011.
- [32] F. M. Malvestuto, M. Mezzini, and M. Moscarini, "Minimal invariant sets in a vertex-weighted graph," *Theoretical Computer Science*, vol. 362, no. 1-3, pp. 140-161, Oct. 2006.
- [33] V. T. Ta, O. Lezoray, and A. Elmoataz, "Graph Based Semi and Unsupervised Classification and Segmentation of Microscopic Images," *2007 IEEE International Symposium on Signal Processing and Information Technology*, Dec. 2007.
- [34] C. Jiang and F. Coenen, "Graph-based Image Classification by Weighting Scheme," *Applications and Innovations in Intelligent Systems XVI*, pp. 63-76, 2009.
- [35] V. R. Parihar, and N. V. Thakur, "Graph Theory Based Approach For Image Segmentation Using Wavelet Transform," *International Journal of Image Processing (IJIP)*, vol. 8, no. 5, pp. 255-277, Sept 2014
- [36] V. R. Parihar, R. S. Nage, and A. S. Dahane, "Image Analysis and Image Mining Techniques: A Review," *Journal of Image Processing and Artificial Intelligence (MAT Journals)*, vol. 3, no. 2, pp. 1-18, June 2017
- [37] V. R. Parihar, and A. P. Dhote, "Overview and an Approach to Real Time Face Detection and Recognition," *International Advanced Research Journal in Science, Engineering and Technology (IARJSET)*, vol. 4, no. 9, pp. 39-46, Sept 2017
- [38] V. R. Parihar, and A. P. Dhote, "Real Time Face Detection and Recognition: Overview and Suggested Approach," *Journal of Image Processing and Artificial Intelligence (MAT Journals)*, vol. 3, no. 3, pp. 1-6, Sept 2017

[39] V. R. Parihar, and A. P. Dhote, "A Novel Approach to Real Time Face Detection and Recognition," *International Journal of Computer Sciences and Engineering*, vol. 5, no. 9, pp. 62-67, Sep. 2017.

[40] A. P. Dhote, V. R. Parihar, R. P. Sonar, and R. S. Nage, "A novel system of real time hand tracking and gesture recognition," *2017 International Conference on Inventive Computing and Informatics (ICICI)*, Nov. 2017



**Prof. Roshani S. Nage** is Assistant Professor in Electrical Engineering Department, PRMCEAM, Badnera-Amravati having 3 years of experience. She has received the B.E degree in Electronics and Telecommunication Engineering from Sant Gadge Baba Amravati University, India, in 2012 and the M.E degree in Electrical and Electronics Engineering, from Sant Gadge Baba Amravati University, India, in 2014. Her domain of research includes Digital Integrated Circuits, Control Systems, Digital Signal Processing, Digital Image Processing. She has published 3 research papers in National/International Journals and conferences.



**Prof. Vikram Singh R. Parihar** is an Assistant Professor in Electrical Department, PRMCEAM, Badnera-Amravati having 6 years of experience. He has received the B.E degree in Instrumentation from Sant Gadge Baba Amravati University, India, in 2011 and the M.E degree in Electrical and Electronics Engineering, Sant Gadge Baba Amravati University, India, in 2014. He is editorial board member of 25 recognized journals and life member of ISTE, HKSME, ICSES, IJCSE and the IRED. His domain of research includes Electrical Engineering, Instrumentation, Electrical Power Systems, Electrical and Electronics Engineering, Digital Image Processing, Neuro Fuzzy Systems and has contributed to research in a commendable way by publishing 40 research papers in National/International Journals and 4 papers in IEEE Conferences.



**Prof. Atul S. Dahane** is Assistant Professor in Electrical Engineering Department, PRMCEAM, Badnera-Amravati having 6 years of experience. He has received the B.Tech. degree in Electrical Engineering from Sant Gadge Baba Amravati University, India, in 2010 and the M.Tech. degree in Electrical Power Systems, from Pune University, India, in 2012. He is a Life Member of ISTE a Technical Association India. His domain of research includes Power System Analysis, Digital Protection, FACTS Technology, Power Electronics. He has published 2 research papers each in International Journal and IET International conference.